

LIFEBOOK T904 vs. T935 Detailed Spec Comparison...



Changes in **RED**

	LIFEBOOK T904	LIFEBOOK T935
Display Type	13.3" WQHD (2560x1440) IGZO backlit ultra durable display	13.3" WQHD (2560x1440) or FHD (1920x1080) IGZO backlit ultra durable display
Display Input	Dual Digitizer (Wacom) - up to 10 finger input and active digitizer (pen input)	Dual Digitizer (Wacom) - up to 10 finger input and active digitizer (pen input)
Processors	4 th generation Intel Core ULT processors; i5 and i7	5th generation Intel Core ULT processors; i5 and i7
Graphics	Intel UMA (Intel® HD Graphics 4400)	Intel UMA (Intel® HD Graphics 5500)
Memory	DDR3L 1600 MHz, Up to 8 GB	DDR3L 1600 MHz, Up to 8 GB
	TCG Opal Compliant Self-encrypted Drive (SED) HDD (5400 rpm): 320GB Hybrid HDD (16 GB Cache): 320, 500GB TCG Opal Compliant Self-encrypted Drive (SED) SSD: 128, 256GB non-FDE SSD: 128, 256GB	TCG Opal Compliant Self-encrypted Drive (SED) HDD (5400 rpm): 320GB Hybrid HDD (16 GB Cache): 320, 500GB TCG Opal Compliant Self-encrypted Drive (SED) SSD: 128, 256GB non-FDE SSD: 128, 256GB
Webcam	2.0 MP, Full HD (1080p) with "ON" LED indicator	2.0 MP, Full HD (1080p) with "ON" LED indicator
Sensors	Accelerometer, gyrometer, magnetometer, ambient light sensor	Accelerometer, gyrometer, magnetometer, ambient light sensor
WWAN support	Integrated 4G Sierra Wireless AirPrime™ EM7355 with GPS support	Integrated 4G Sierra Wireless AirPrime™ EM7355 with GPS support
OS	Windows 8 .1 Pro (64 preinstalled, 32-bit drivers only) Windows 7 Professional (64)	Windows 8 .1 Pro (64 preinstalled, 32-bit drivers only) Windows 7 Professional (64)
Buttons	2 button + Windows button + power switch	2 button + Windows button + power switch

... LIFEBOOK T904 vs. T935 Detailed Spec Comparison



Changes in **RED**

Model	LIFEBOOK T904	LIFEBOOK T935
Communication	LAN (RJ-45, pull out cable) Intel® Dual Band Wireless-N 7260 (802.11 a/b/g/n) Bluetooth v4.0	LAN (RJ-45, pull out cable) Intel® Dual Band Wireless-AC 7265 (802.11ac/a/b/g/n) Bluetooth® 4.0
Expandability	SD slot, HDMI, 2 USB 3.0 (1x anytime charge), SmartCard slot, port replicator connector	SD slot, HDMI, 2 USB 3.0 (1x anytime charge), SmartCard slot, port replicator connector
Modular Bay	N/A, Main Battery is removable	N/A, Main Battery is removable
Security	Fingerprint, TPM, Computrace BIOS agent, security panel, integrated SmartCard slot, PBA, iAMT support (vPro technology), Anti-theft lock slot	Fingerprint, TPM, Computrace BIOS agent, security panel, integrated SmartCard slot, PBA, iAMT support (vPro technology), Anti-theft lock slot
Battery Specification	4cell (10.8V 72 Wh) – 9 hrs and 30 mins	4cell (10.8V 72 Wh) – TBD
Port Replicator	VGA, DVI-D, Display Port, 4 x USB 3.0, RJ-45, Audio- Out, DC-in, Power button, Undock release lever	VGA, DVI-D, Display Port, 4 x USB 3.0, RJ-45, Audio- Out, DC-in, Power button, Undock release lever
Dimensions & Weight	12.64" (w) x 9.25" (d) x 0.67/0.76" 3.51 lbs.	12.64" (w) x 9.25" (d) x 0.67/0.76" 3.51 lbs.